

max. 200W - IIC - max. T6









Features



| | |
|--------------------------|--|
| Certificate | IECEX TUR 15.0022X, TÜV 14 ATEX 7567 X |
| Zone | 1, 21 |
| Temperature range | -40 °C - 55 °C |
| Voltage | 230 V |
| Material | Brass |

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| WISKA-No. | Type | Marking | Power | Protection class to EN 60 529 | Lampholder | Temp.-class |  |
|-----------|------------------------|--|------------|-------------------------------|------------|-------------|---|
| 10031802 | Ex-3314/2/E27/20 | II 2G Ex d IIC T6...T3 Gb, II2D Ex tbIIIC T85...T200°C Db | max. 200 W | IP66/67 | E27 | max. T6 |  |
| 10031806 | Ex-3314/2/E27/22W/20 | II2D Ex tbIIIC T85...T200°C Db, II 2G Ex d IIC T6...T3 Gb | 1 x 22 W | IP66/67 | E27 | max. T6 |  |
| 10031257 | Ex-3312/D/B22/2x24-Z14 | II 2G Ex de IIC T6...T3 Gb, II2D Ex tbIIIC T85...T200°C Db | max. 200 W | IP66/67 | B22d | max. T6 |  |
| 10031254 | Ex-3312/D/E27/2x24-Z14 | II2D Ex tbIIIC T85...T200°C Db, II 2G Ex de IIC T6...T3 Gb | max. 200 W | IP66/67 | E27 | max. T6 |  |
| 10104849 | Ex-3312/D/E27/2x20-Z10 | II2D Ex tbIIIC T85...T200°C Db, II 2G Ex de IIC T6...T3 Gb | max. 200 W | IP66/67 | E27 | max. T6 |  |