

EMSKE








Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



Features



Marking	II 2 G Ex e IIC Gb / II 2 D Ex tb IIIC Db IP68
Approval	IECEx PTB 13.0027X / PTB 04 ATEX 1112 X
Protection class	IP66/IP68 (5 bar 30 min)
Temperature range	-40 °C - 75 °C
Surface	Nickel-plated
Material	Screw: Brass nickel-plated, Clamping cage Polyamide, Gasket EPDM

WISKA-No.	Type	 D (mm)	 (mm)	 (mm)	 SW (mm)	TL (mm)	
10065040	EMSKE 12	M 12x1,5	5 mm	4 mm - 7 mm	16 mm	23 mm - 30 mm	50
10065041	EMSKE 16	M 16x1,5	5 mm	5 mm - 10 mm	20 mm	26 mm - 34 mm	50
10065042	EMSKE 20	M 20x1,5	6 mm	6 mm - 13 mm	24 mm	29 mm - 37 mm	50
10065043	EMSKE 25	M 25x1,5	7 mm	10 mm - 17 mm	29 mm	33 mm - 42 mm	50
10065044	EMSKE 32	M 32x1,5	8 mm	13 mm - 21 mm	36 mm	36 mm - 44 mm	25
10065045	EMSKE 40	M 40x1,5	8 mm	16 mm - 28 mm	46 mm	44 mm - 55 mm	10
10065046	EMSKE 50	M 50x1,5	9 mm	21 mm - 35 mm	55 mm	51 mm - 62 mm	10
10065047	EMSKE 63	M 63x1,5	10 mm	34 mm - 48 mm	68 mm	56 mm - 67 mm	10
10104386	EMSKE 75	M 75x1,5	12 mm	48 mm - 62 mm	82 mm	67 mm - 81 mm	1