

SPRINT NMSKE, brass, NPT





Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



Features



Marking	II 2 D Ex tb IIIC Db IP68 / II 2 G Ex e IIC Gb
Approval	IECEx PTB 13.0027X / PTB 04 ATEX 1112 X
Protection class	IP66/IP68 (5 bar 30 min)
Temperature range	-40 °C - 75 °C
Surface	Nickel-plated
Material	Screw: Brass nickel-plated, Clamping cage Polyamide, Gasket EPDM

WISKA-No.	Type	 D (mm)	 (mm)	 (mm)	 SW (mm)	TL (mm)	
10101082	NMSKE 1/4	NPT 1/4"	13 mm	4 mm - 7 mm	16 mm	33 mm - 40 mm	50
10101083	NMSKE 3/8	NPT 3/8"	13 mm	5 mm - 10 mm	20 mm	35 mm - 42 mm	50
10101084	NMSKE 1/2	NPT 1/2"	16 mm	6 mm - 13 mm	24 mm	38 mm - 45 mm	50
10101085	NMSKE 3/4	NPT 3/4"	16 mm	10 mm - 17 mm	29 mm	40 mm - 48 mm	50
10101086	NMSKE 1	NPT 1"	20 mm	13 mm - 21 mm	36 mm	46 mm - 53 mm	25
10101087	NMSKE 1 1/4	NPT 1 1/4"	20 mm	16 mm - 28 mm	46 mm	50 mm - 58 mm	10
10101088	NMSKE 1 1/2	NPT 1 1/2"	20 mm	21 mm - 35 mm	55 mm	51 mm - 62 mm	10
10101089	NMSKE 2	NPT 2"	21 mm	34 mm - 48 mm	68 mm	56 mm - 67 mm	10