

ESSKE, stainless steel 1.4305



Features



Marking	II 2 G Ex e IIC Gb / II 2 D Ex tb IIIC Db IP68
Approval	IECEx PTB 13.0035X / PTB 05 ATEX 1098 X
Protection class	IP66 / IP68 (5 bar 30 min)
Temperature range	-40 °C - 75 °C
Material	Clamping cage Polyamide, Gasket EPDM

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



WISKA-No.	Type	 D (mm)	 L (mm)	 (mm)	 SW (mm)	TL (mm)	
10069200	ESSKE 12	M 12x1,5	5 mm	4 mm - 7 mm	17 mm	23 mm - 30 mm	10
10069201	ESSKE 16	M 16x1,5	5 mm	5 mm - 10 mm	22 mm	26 mm - 34 mm	10
10069202	ESSKE 20	M 20x1,5	6 mm	6 mm - 13 mm	24 mm	29 mm - 37 mm	10
10069203	ESSKE 25	M 25x1,5	7 mm	10 mm - 17 mm	30 mm	33 mm - 42 mm	10
10069204	ESSKE 32	M 32x1,5	8 mm	13 mm - 21 mm	36 mm	36 mm - 44 mm	5
10069205	ESSKE 40	M 40x1,5	8 mm	16 mm - 28 mm	46 mm	44 mm - 55 mm	5
10069206	ESSKE 50	M 50x1,5	9 mm	21 mm - 35 mm	55 mm	51 mm - 62 mm	2
10069207	ESSKE 63	M 63x1,5	10 mm	34 mm - 48 mm	68 mm	56 mm - 67 mm	1