

EX d OSNJ NPT, brass, for non-armoured cables, NPT







Features



Marking	Ex d IIC / Ex e II, Ex tD A21 IP66/IP67
Approval	NEMKO 03 ATEX 1460 X / IECEx KOS 09.0017X
Protection class	IP67
Temperature range	-20 °C - 120 °C
Material	Screw: Brass nickel-plated

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



WISKA-No.	Type	Surface	 D (mm)	 L (mm)	 (mm)	
50065721	OSNJ A2F-16a / NPT 1/2"	Nickel-plated	NPT 1/2"	15 mm	3 mm - 7,5 mm	1
50065722	OSNJ A2F-16b / NPT 1/2"	Nickel-plated	NPT 1/2"	15 mm	6,1 mm - 10 mm	1
50065723	OSNJ A2F-20a / NPT 1/2"	Nickel-plated	NPT 1/2"	15 mm	10 mm - 13 mm	1
50065724	OSNJ A2F-20b / NPT 1/2"	Nickel-plated	NPT 1/2"	15 mm	13,1 mm - 15 mm	1
50065725	OSNJ A2F-25a / NPT 3/4"	Nickel-plated	NPT 3/4"	15 mm	14 mm - 17,5 mm	1
50065726	OSNJ A2F-25b / NPT 3/4"	Nickel-plated	NPT 3/4"	15 mm	16,1 mm - 19,5 mm	1
50065727	OSNJ A2F-32a / NPT 1"	Nickel-plated	NPT 1"	15 mm	18,1 mm - 22 mm	1
50065728	OSNJ A2F-32b / NPT 1"	Nickel-plated	NPT 1"	15 mm	21 mm - 26 mm	1
50065729	OSNJ A2F-40a / NPT 1-1/4"	Nickel-plated	NPT 1 1/4"	15 mm	24 mm - 28 mm	1
50065730	OSNJ A2F-40b / NPT 1-1/4"	Nickel-plated	NPT 1 1/4"	15 mm	27 mm - 32 mm	1
50065731	OSNJ A2F-50a / NPT 1-1/2"	Nickel-plated	NPT 1 1/2"	15 mm	32,1 mm - 34 mm	1
50065732	OSNJ A2F-50b / NPT 1-1/2"	Nickel-plated	NPT 1 1/2"	15 mm	34,1 mm - 40 mm	1