

COMBI 304

Features

COMBI

habeign




Protection class	IP66 / IP67
Glow wire test	750 °C
Temperature range	-30 °C - 100 °C
Installation temperature	-5 °C - 60 °C
Voltage	400 V
Material	Polypropylene, Gasket TPE



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



WISKA-No.	Type	RAL-No.	LxBxH außen (mm)	
10110629	COMBI 304 LG	RAL 7035	Ø 82 x 57mm	5
10110630	COMBI 304 BK	RAL 9005	Ø 82 x 57mm	5
10110631	COMBI 304 WH	RAL 9001	Ø 82 x 57mm	5
10110632	COMBI 304/5 LG	RAL 7035	Ø 82 x 57 mm	5
10110633	COMBI 304/5 BK	RAL 9005	Ø 82 x 57 mm	5
10110634	COMBI 304/5 WH	RAL 9001	Ø 82 x 57 mm	5
10110635	COMBI 304 / 3-221-413 LG	RAL 7035	Ø 82 x 57mm	5
10110636	COMBI 304 / 3-221-413 BK	RAL 9005	Ø 82 x 57mm	5
10110637	COMBI 304 / 3-221-413 WH	RAL 9001	Ø 82 x 57mm	5

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.com · www.wiska.com

Other technical data on request / subject to change without notice