

LED Multi-purpose Luminaire 4010



Type	4010-1X8-230-2-CC	4010-1X8-24-2-CC	4010-2X8-230-2-CC	4010-2X8-24-2-CC	4010-3X8-230-2-CC	4010-1X16-230-2-CC	4010-2X16-230-2-CC	4010-3X16-230-2-CC	4010-2X8-230-2-CC-E02	4010-2X18-230-2-CC-E02
WISKA Order no.	10111887	10111893	10111888	10111894	10111889	10111890	10111891	10111892	10111895	10111896
Short / Long Version	Short	Short	Short	Short	Short	Long	Long	Long	Short	Long
Dimensions (mm)	495x185x78	495x185x78	495x185x78	495x185x78	495x185x78	775x185x78	775x185x78	775x185x78	595x185x78	875x185x78
IP Rating	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67	IP66/67
Material	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Impact Rating	IK10	IK10	IK10	IK10	IK10	IK10	IK10	IK10	IK10	IK10
Voltage	230 V	24 V	230 V	24 V	230 V	230 V	230 V	230 V	230 V	230 V
Number of LED Stripes	1	1	2	2	3	1	2	3	2	2
Wattage	8 W	8 W	16 W	16 W	24 W	16 W	32 W	49 W	16 W	32 W
Luminous Flux	1,200 lm	1,200 lm	2,400 lm	2,400 lm	3,600 lm	2,400 lm	4,800 lm	7,200 lm	2,400 lm	4,800 lm
Colour Temp	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K	4,000 K
Beam Type	Wide	Wide	Wide	Wide	Wide	Wide	Wide	Wide	Wide	Wide
Temperature Range	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C	-25 °C · 50 °C
Mounting	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling
Rated Lifetime	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C	L70/B10@Ta +45 °C
System Lifetime	50,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours	100,000 hours
Back up Battery	No	No	No	No	No	No	No	No	Yes	Yes
Description	Short version, 1 x LED strip 1,200 lm 230 V	Short version 1 x LED strip 1,200 lm 24 V	Short version 2 x LED strips 2,400 lm 230 V	Short version 2 x LED strips 2,400 lm 24 V	Short version 3 x LED strips 3,600 lm 230 V	Long version 1 x LED strip 2,400 lm 230 V	Long version 2 x LED strips 4,800 lm 230 V	Long version 1 x LED strip 7,200 lm 230 V	Short version 2 x LED strips 2,400 lm 230 V Back up Battery	Long version 2 x LED strips 4,800 lm 230 V Back up Battery