



CEILING LUMINAIRE FOR RECESSED INSTALLATION  
IN PANEL CEILINGS (DAMPA DCC300)

<b>Design</b>	According to rules of maritime classification societies and relevant standards
<b>Housing</b>	Galvanized steel, powder coated white (RAL9016)
<b>Diffuser</b>	Clear polycarbonate with ice crystal or prismatic structure or parabolic louver
<b>Mounting</b>	Mounting brackets and side rails
<b>Cable entry</b>	2 inlets for cables max. Ø 11 mm
<b>Protection class</b>	IP20 / IP44 in conjunction with ceiling, IP20 with louver
<b>Weight</b>	5.4 kg
<b>Light source</b>	Linear LP LED modules
<b>Wattage</b>	Max. 20 W
<b>CCT (color)</b>	3,000 K or 4,000 K
<b>Luminous flux</b>	1,500 lm
<b>CRI</b>	≥ 80
<b>Voltage</b>	220–240 V AC
<b>Frequency</b>	50–60 Hz

**PART NO.**

DE95 DCC S

5111009410-xxx

**SPARE PARTS**

**PART NO.**

Ice crystal cover (DE95 DCC S) 7931001300

**EXTRAS**

- > 120 V AC execution
- > 24 V DC execution
- > Dimmable
- > Emergency battery back-up
- > Alternative housing colors
- > Different diffusers available

