

COMBI MAR 304/181/4xESKV 20 BK

Junction box, round Ø 82 x 57mm, Polypropylene, RAL 9005, with terminal + 4xESKV



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



Material	Polypropylene
Material sealing gasket	TPE
Temp. range min	-30 °C
Temp. range max	100 °C
Temperatures during install.	-5 °C - 60 °C
Protection class	IP66 / IP67
Glow wire test	960 °C
Voltage	400 V
Rated current / A (Terminal)	32 A
Rated cross section	4 mm ²
Terminals/poles	5-pole, 4,0 mm ²
Fixing	4 internal openings
Ø cable diameter min	3 mm
Ø cable diameter max	12 mm
External dimensions LxWxH	Ø 82 x 57 mm
Type of cable gland	M 20 x 1,5
Product Color	RAL 9005
WISKA-Order no.	10111066
Type	COMBI MAR 304/181/4xESKV 20 BK
Packing unit	1
ETIM-Classification	EC002600

Remarks:

IP66: using the membrane entry

IP67: using the threaded entry together with ESKV cable gland

Equipment:

- 4x M20 threaded membrane entries
- incl. 4 cable glands 6-13mm
- terminals: 4-pole, 2,5mm²

Spare parts

SP-181/4 Terminal block

22000352

30.08.2024