

max. 200W - IIC - max. T6








Features



Certificate	IECEX TUR 15.0022X, TÜV 14 ATEX 7567 X
Zone	1, 21
Temperature range	-40 °C - 55 °C
Voltage	230 V
Material	Brass

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



WISKA-No.	Type	Marking	Power	Protection class to EN 60 529	Lampholder	Temp.-class	
10031802	Ex-3314/2/E27/20	II 2G Ex d IIC T6...T3 Gb, II2D Ex tbIIIC T85...T200°C Db	max. 200 W	IP66/67	E27	max. T6	
10031806	Ex-3314/2/E27/22W/20	II2D Ex tbIIIC T85...T200°C Db, II 2G Ex d IIC T6...T3 Gb	1 x 22 W	IP66/67	E27	max. T6	
10031257	Ex-3312/D/B22/2x24-Z14	II 2G Ex de IIC T6...T3 Gb, II2D Ex tbIIIC T85...T200°C Db	max. 200 W	IP66/67	B22d	max. T6	
10031254	Ex-3312/D/E27/2x24-Z14	II2D Ex tbIIIC T85...T200°C Db, II 2G Ex de IIC T6...T3 Gb	max. 200 W	IP66/67	E27	max. T6	
10104849	Ex-3312/D/E27/2x20-Z10	II2D Ex tbIIIC T85...T200°C Db, II 2G Ex de IIC T6...T3 Gb	max. 200 W	IP66/67	E27	max. T6	