

## EX d cable glands for non-armoured cables, OSNJ, brass nickel-plated, metric



### Features



<b>Marking</b>	Ex d IIC / Ex e II, Ex tD A21 IP66/IP67
<b>Approval</b>	IECEX KOS 09.0017X / NEMKO 03 ATEX 1460 X
<b>Protection class</b>	IP67
<b>Temperature range</b>	-20 °C - 120 °C
<b>Material</b>	Brass nickel-plated, Gasket Silicone

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



WISKA-No.	Type	Surface	 D (mm)	 H (mm)	 (mm)	 SW (mm)	
50065500	OSNJ A2F-16a / M16	Nickel-plated	M 16x1,5	15 mm	3 mm - 7,5 mm	24 mm	1
50065501	OSNJ A2F-16b / M16	Nickel-plated	M 16x1,5	15 mm	6,1 mm - 10 mm	24 mm	1
50065502	OSNJ A2F-20a / M20	Nickel-plated	M 20x1,5	15 mm	10 mm - 13 mm	27 mm	1
50065503	OSNJ A2F-20b / M20	Nickel-plated	M 20x1,5	15 mm	13,1 mm - 15 mm	27 mm	1
50065504	OSNJ A2F-25a / M25	Nickel-plated	M 25x1,5	15 mm	14 mm - 17,5 mm	32 mm	1
50065505	OSNJ A2F-25b / M25	Nickel-plated	M 25x1,5	15 mm	16,1 mm - 19,5 mm	32 mm	1
50065506	OSNJ A2F-32a / M32	Nickel-plated	M 32x1,5	15 mm	18,1 mm - 22 mm	39 mm	1
50065507	OSNJ A2F-32b / M32	Nickel-plated	M 32x1,5	15 mm	21 mm - 26 mm	39 mm	1
50065508	OSNJ A2F-40a / M40	Nickel-plated	M 40x1,5	15 mm	24 mm - 28 mm	48 mm	1
50065509	OSNJ A2F-40b / M40	Nickel-plated	M 40x1,5	15 mm	27 mm - 32 mm	48 mm	1
50065510	OSNJ A2F-50a / M50	Nickel-plated	M 50x1,5	15 mm	32,1 mm - 34 mm	58 mm	1
50065511	OSNJ A2F-50b / M50	Nickel-plated	M 50x1,5	15 mm	34,1 mm - 40 mm	58 mm	1
50065512	OSNJ A2F-63a / M63	Nickel-plated	M 63x1,5	15 mm	38 mm - 44 mm	73 mm	1
50065513	OSNJ A2F-63b / M63	Nickel-plated	M 63x1,5	15 mm	43 mm - 50 mm	73 mm	1
50065514	OSNJ A2F-63c / M63	Nickel-plated	M 63x1,5	15 mm	49 mm - 54 mm	73 mm	1
50065515	OSNJ A2F-75a / M75	Nickel-plated	M 75x1,5	15 mm	52 mm - 56 mm	85 mm	1
50065516	OSNJ A2F-75b / M75	Nickel-plated	M 75x1,5	15 mm	55 mm - 60 mm	85 mm	1
50065517	OSNJ A2F-75c / M75	Nickel-plated	M 75x1,5	15 mm	59 mm - 62 mm	85 mm	1
50065518	OSNJ A2F-75d / M75	Nickel-plated	M 75x1,5	15 mm	62,1 mm - 66 mm	85 mm	1