

COMBI IP68 SET (FLUID SEALING)
















Features



Protection class	IP68 (15 m 170 h)
Glow wire test	750 °C
Temperature range	-30 °C - 100 °C
Installation temperature	-5 °C - 60 °C
Filling	Silicone
Material	Polypropylene, Gasket TPE

Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



WISKA-No.	Type	RAL-No.		LxBxH außen (mm)	
10060457	COMBI IP 68 SET 308	RAL 7035		85 x 85 x 51 mm	1
10066634	COMBI IP 68 SET 308/5	RAL 7035		85 x 85 x 51 mm	1
10105681	COMBI IP 68 SET 407	RAL 7035		95 x 95 x 60 mm	1
10105682	COMBI IP 68 SET 407/5	RAL 7035		95 x 95 x 60 mm	1
10105683	COMBI IP 68 SET 407/S	RAL 9005		95 x 95 x 60 mm	1
10105684	COMBI IP 68 SET 407/5/S	RAL 9005		95 x 95 x 60 mm	1
10061185	COMBI IP 68 SET 607	RAL 7035		110 x 110 x 66 mm	1
10066635	COMBI IP 68 SET 607/5	RAL 7035		110 x 110 x 66 mm	1
10100838	COMBI IP 68 SET 607/S	RAL 9005		110 x 110 x 66 mm	1
10061488	COMBI IP 68 SET 1010	RAL 7035		140 x 140 x 82 mm	1
10066636	COMBI IP 68 SET 1010/5	RAL 7035		140 x 140 x 82 mm	1