



IBS Industry Boxes System, stainless steel 1.4301 (V2A/SUS 304)



Protection class to EN 60 529: IP 66/67

Material: 1,5 mm special steel 1.4301 (V2A/SUS 304), completely welded, powder coated RAL 7032

Temperature resistance: -40°C up to 120°C

Equipment: - Earthing bolts inside and outside

- Indestructible allround cover seal

- Protection specification acc. to EN 50102 (external mechanical impacts): IK 08

Fixing: 4 mounting links with oblong holes $\varnothing 9 \times 15$ mm

Variations: - Integrated module holder rails and mounting plates

- Mounting of cable glands

- Special dimensions and colours on request

IBS Industriekasten-System, Edelstahl 1.4301 (V2A/SUS 304)

Schutzart gemäß EN 60 529: IP 66/67

Material: 1,5 mm Edelstahl 1.4301 (V2A/SUS 304), komplett geschweißt, Pulver beschichtet RAL 7032

Temperaturbeständigkeit: -40°C bis 120°C

Ausstattung: - Erdungsbolzen innen und außen

- Unzerstörbare, umlaufende Deckelprofildichtung

- Schutzart gegen äußere mechanische Beanspruchung: IK 08

Befestigung: 4 Befestigungsglaschen mit Langloch $\varnothing 9 \times 15$ mm

Varianten: - Einbau von Tragschienen oder Montageplatten

- Einbau von Kabelverschraubungen

- Sondergrößen und -farben

Type	L x W x H external/außen	L x W x H internal/innen	X x Y
	[mm]	[mm]	[mm]
IBS-151508	190x156x100	130x130x77	172x125
IBS-301508	340x156x100	280x130x77	322x125
IBS-202008	240x206x100	180x180x77	222x175
IBS-302008	340x206x100	280x180x77	322x175
IBS-402012	440x206x140	380x180x117	422x175
IBS-303012	340x306x140	280x280x117	322x275
IBS-302015	340x206x170	280x180x147	322x175

For the wide range of Cable glands and accessories for all applications please look at the catalogue "WISKA INDUSTRY"
Das umfangreiche Sortiment an Kabelverschraubungen und Zubehör für alle Einsatzbereiche finden Sie im Katalog "WISKA INDUSTRY".